



GFA1672C

TECHNICAL DATA:

Power: 15W

Lumen: 1200lm

Color Temperature: 3000K

Power Supply: 220-240V AC _ 50/60Hz

IP Rating: IP20

Light Beam: 40° _ Orientabile

CRI: >80

Lifespan: 50.000h

Insulation Class: I

Installation: Interno _ Incasso

Source: Led integrato

Dimming: Non dimmerabile _ On - Off

Energy Class: E

Volume: 0,0012m³

Gross Weight: 0.44 Kg

Net Weight: 0.40 Kg

Proiettore a binario Eurostandard. Struttura in alluminio pressofuso. Riflettore in alluminio brillantato. Finitura in bianco opaco. Diffusore in policarbonato trasparente. Modulo LED CREE e trasformatore incluso.

Eurostandard track-mounted projector. Die-cast aluminium structure. Polished aluminium reflector. Matt white finish. Transparent polycarbonate diffuser. CREE LED module and transformer included.

Projecteur sur rail Eurostandard. Structure en aluminium moulé sous pression. Réflecteur en aluminium poli. Finition blanc mat. Diffuseur en polycarbonate transparent. Module LED CREE et transformateur inclus.

Schiennenmontierter Eurostandard-Projektor. Struktur aus Aluminiumdruckguss. Reflektor aus poliertem Aluminium. Mattweißes Finish. Diffusor aus transparentem Polycarbonat. CREE-LED-Modul und Transformator im Lieferumfang enthalten.

